




**ETAGE**  
Hängande textil




## ETAGE

Hängande textil


### Material 100% Polyester FR




0080




0081




0083




0056




0082




0061




0048



0064



0059

	Öppningsfaktor %	Vikt	Skarvfri vid höjd lägre än	Ljushårdighet ISO 105-B02 (skala 1-8)	Flamskyddad 	Ljudabsorbktion ISO 354 (skala 0-1)	SOLAR Rs (B = b-sida)	SOLAR As (B = b-sida)	Vändbar
0080	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	55	45	Ja
0081	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	55	45	Ja
0083	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	55	45	Ja
0056	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	45	55	Ja
0082	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	55	45	Ja
0061	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	40	60	Ja
0048	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	55	45	Ja
0064	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	40	60	Ja
0059	Dim-out	260 g/m <sup>2</sup>	2760 mm	5	EN 13773 class 1	0,70 (C)	35	65	Ja

#### Skötselråd:



Krympning vid 60° < 2%

Kan tvättas i 70°

